

GUIDELINES FOR CHOOSING A MOTOR



		ELECTRONIC MOTOR WITH INTEGRATED RADIO CONTROLS								ELECTRONIC MOTOR WITH WIRED CONTROLS						SHORT ELECTRONIC MOTOR	CONTROL UNITS*					STANDARD MOTOR WITH MECHANICAL LIMIT SWITCH*								
		SENSO RX 35 mm	WAVE RX 45/58 mm	SENSO RX 45 mm	WAVE RX V25 45/58 mm	TRONIC RX 35 mm	TRONIC RX 45/58 mm	CLIMA PLUS RX 45/58 mm	CLIMA RX 45/58 mm	PLUG&PLAY PLUS 35 mm	PLUG&PLAY PLUS 45 mm	PLUG&PLAY 3000 45 mm	PLUG&PLAY 45 mm	WAVE WIRE 45/58 mm	SENSO WIRE 45 mm	PLUG&PLAY OCEAN EASY 45 mm	PLUG&PLAY SHORT 45 mm	PLUG&PLAY SHORT RX 45 mm	TDS COMPACT	TDS GOLD	TDS SILVER	OPTIME / COMPACT ROLL	MIRROLL	MINI	GARDA 45/58 mm	ROLL 35/45 mm	ROLL EASY 45 mm	MICRO 45 mm	MICRO EASY 45 mm	OCEAN 45/58 mm
APPLICATION	Roller screen	•	•	•	•					•	•			•	•				•	•	•	•		•		•				•
	Awnings		•		•									•					•	•	•			•						•
	Pergola		•		•									•					•	•	•			•						•
	Rolling shutters					•	•			•	•	•	•			•	•	•				•	•	•	•	•	•	•	•	•
	Adjustable shutters							•	•																					
REMOTE CONTROL		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•						
WIRED SWITCH		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
BUTTON PROGRAMMING		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•						
OBSTACLE DETECTION WHEN ASCENDING		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				•							
OBSTACLE DETECTION WHEN DESCENDING	Soft hangers										•																			
	Hard hangers					•	•	•	•	•	•	•																		
RETURN WITH OBSTACLE						•	•	•	•	•	•	•																		
RELEASE ON UPPER END STOP						•	•	•	•	•	•	•																		
SUPER SENSITIVITY		•	○	•	○	•					•		○	•					•				•							
OPTIMIZED FABRIC TENSIONER			•		•																									
CLOSING FORCE ADJUSTMENT		•	•	•	•	•	•	•	•					•					•				•							
INTERMEDIATE POSITION		•	•	•	•	•	•	•	•										•				•							
AUTOMATIC COUPLING AND UNCOUPLING					•																									
BLIND ADJUSTMENT MANAGEMENT							•	•																						
CLIMATIC CONTROLS		•	•	•	•														•	•	•			•						
OVERRIDE DEVICE																•														•
REDUCED LENGTH																	•	•									•	•		
QUICK CONNECTION																							(•)			•	•	•		
HEAD WITH SINTERED STEEL CLAMP (only Ø45 up to 15 Nm)						•				•	•	•					•	•												

See the "automation system compatibility table" (page 96) for the mechanical limit switch motor + control unit combinations

* See the "automation system compatibility table" (page 96) for the mechanical limit switch motor + control unit combinations.

○ Up to 25 Nm